

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FS-8P-M16XL/1,5 1571162 PHOENIX CONTACT

Conect. plug. to be apar. wall poster., Universal, 8-pol..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FS-8P-M16XL/1,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FS-8P-M16XL/1,5
Catalog number	1571162
Category	Circular connector, mounting (with cable)
Minimum order	1000 Pcs
Document ID	EO-B3299206D3
Generated	2026-08-05

Product Overview

Conect. plug. to be apar. wall poster., Universal, 8-pole, Female connection, straight, M12-Standard, coding: A, to free cable end, Rear wall mounting, M16 x 1.5, Single stranded wires, cable length: 1.5 m, 0.25 mm², TPE braided wire
Connect. plug in. to apar. wall poster.

Device connector, rear mounting, Universal, 8-position, Socket, straight, M12-Standard, coding: A, on free cable end, Rear mounting, M16 x 1.5, Individual wires, cable length: 1.5 m, 0.25 mm², TPE litz wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesGeneral The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

General Lock nut is included in the scope of delivery

General Contact connection method: Crimp connection

MountingMounting type Rear mounting M16 x 1.5 With flat nut, tightening limitation

Assembly instructions With flat nut, tightening limitation

Connection method Individual wires

Product propertiesProduct type Circular connectors (device side)

Sensor type Universal

Number of positions 8
No. of cable outlets 1
Shielded no
Coding A
Thread type M12
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specifications Flammability rating according to UL 94 V0
Seal material FKM
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material for screw connection Zinc die-cast, nickel-plated
Conductor material Tin-plated Cu litz wires
Electrical properties Rated surge voltage 0.8 kV
Contact resistance $\leq 3 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V (AC)
30 V (DC)
Nominal current IN 2 A
Max. conductor resistance 80 m Ω /m
Connection data Conductor connection
Connection method Individual wires
Contact connection type Socket
Conductor cross section 0.25 mm²
Tigh...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FS-8P-M16XL/1,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.