

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FSL-4CON-M16XL/0,2 1425589 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FSL-4CON-M16XL/0,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FSL-4CON-M16XL/0,2
Catalog number	1425589
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-63D01466F2
Generated	2026-08-04

Product Overview

Flush-type connector

Conect. plug. to be apar. wall poster., Power, 4-pole, Built-in mounting female, straight, M12-Standard, L, to free cable end, Rear mounting, M16 x 1.5, Single stranded wires, cable length: 0.2 m, 2.50 mm², PEX conductor, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) 1239520

Device connector rear mounting, Power, 4-position, Socket, straight, M12-Standard, coding: L, on free cable end, Rear mounting, M16 x 1.5, Individual wires, cable length: 0.2 m, 2.50 mm², PEX litz wire, Alternative product in accordance with RoHS II without Exemption 6c (Pb)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Order information: Lock nut is included in the scope of delivery

General Contact connection method: Crimp connection

MountingMounting type Rear mounting M16 x 1.5 XL version, with flat nut, tightening limitation

Assembly note XL version, with flat nut, tightening limitation

Product propertiesProduct type Circular connectors (device side)

Sensor type Power
Number of positions 4
No. of cable outlets 1
Shielded no
Coding L
Thread type M12
Data management status
Article revision 10
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Material specifications Flammability rating according to UL 94 V0
Seal material FKM
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Material for screw connection Zinc die-cast, nickel-plated
Conductor material Tin-plated Cu litz wires
Electrical properties Rated surge voltage 1.5 kV
1.5 kV AC/DC
Nominal voltage UN 63 V DC
Nominal current IN 16 A
Test voltage 1.5 kV
Connection data Conductor connection
Connection method Individual wires
Contact connection type Socket
Conductor cross section 2.5 mm²
Mechanical properties Mechanical dat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FSL-4CON-M16XL/0,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.