

**INDUSTRIAL COMPONENT DATA**

# SACC-DSI-M12FSS-3P-M16/1,0 PEX 1238558 PHOENIX CONTACT Conect. plug. to be apar. Wall poster., Power, 3-pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FSS-3P-M16/1,0 PEX



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | SACC-DSI-M12FSS-3P-M16/1,0 PEX            |
| Catalog number  | 1238558                                   |
| Category        | Circular connector, mounting (with cable) |
| Minimum order   | 50 Pcs                                    |
| Document ID     | EO-E866F890C8                             |
| Generated       | 2026-08-05                                |

## Product Overview

Conect. plug. to be apar. Wall poster., Power, 3-pole, Female connection, M12, coding: S, free cable end, Rear wall mounting, M16 x 1.5, Single stranded wires, cable length: 1 m, 1.31 mm<sup>2</sup>, UL/cUL switching twisted wire, The item does not contain lead according to the RoHS II directive without exception 6c (Pb<0.1 %)

Connect. Plug. to apar. poster wall, Power, 3-pole, Connecting female, M12, S-Power, Rear mount, M16 x 1.5, Single stranded wires, cable length: 1 m, 1.31 mm<sup>2</sup>, UL/cUL switching twisted wire

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

ETIM for 1238558 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

1 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Back wall mounting

Housing material (EF001596)  
Other  
Material core insulation (EF000061)  
Other  
Material of contact surface (EF004020)  
Other  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Ambient temperature (EF002386)  
85 °C  
Operating temperature (EF002393)  
-25 °C  
Rated voltage (EF000228)  
630 V  
With shield connection (EF002535)  
No  
Screw-in thread (EF012303)  
M12  
Core cross section (EF000018)  
1.31 mm<sup>2</sup>  
Min. number of insertion cycles (EF012212)  
100  
Degree of protection (IP), mounted (EF007466)  
Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FSS-3P-M16/1,0 PEX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.