

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FSS-4P-M16/0,5PEMV 1425828 PHOENIX CONTACT Flush-type connector, Power, 4-position, Socket, M12,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FSS-4P-M16/0,5PEMV



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FSS-4P-M16/0,5PEMV
Catalog number	1425828
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-4D3418E2D7
Generated	2026-08-04

Product Overview

Flush-type connector, Power, 4-position, Socket, M12, S power, Rear mounting, M16 x 1.5, Individual wires, UL/cUL stranded hook-up wire

Conect. plug. to be apar. Wall Poster., Power, 4-Pole, Connecting Female, M12, S - Power, Rear Mount, M16 x 1.5, Single Stranded Wires, UL/cUL Switching Twisted Wire, RoHS II Alternative Product Without Exception 6c (Pb< 0.1%) 1239560

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1425828

Packing unit 1

GTIN 4055626429496

Custom tariff number 85444290

Drawings

Ambient conditions

Material

Standards and Regulations

Classifications

Dimensions

General

Connection data

Environmental Product Compliance

Drawings

Dimensional drawing

M12 flush-type socket

Circuit diagram

Contact assignment of the M12 socket

Schematic diagram

Pin assignment of M12 socket, 4-pos., S-coded, socket side view

[Back to top](#)Dimensions

Fixed cable length 0.5

[Back to top](#)Ambient conditions

Ambient temperature (operation) -25 ... -85 (Plug / socket)

[Back to top](#)General

Standards/regulations M12 connector In line with

Design Pin

Tightening torque nut 3 Nm ... 4 Nm (M12 connector)

Insertion/withdrawal cycles > 100

Overvoltage category III

Mounting type Rear mounting

Coding S power

Thread type M16 x 1.5

Cable cross section 1.31

AWG signal line 16

Rated surge voltage 6 kV AC

Degree of pollution 3

Degree of protection IP67

Number of positions 4

Current 12 A

Voltage 630 V

[Back to top](#)Material

Contact material CuZn

Contact surface material Au

Flammability rating according to UL 94 V0

[Back to top](#)Connection data

Connection method Individual wires

Contact resistance with connected conductor <= 3 m?

Cable type UL/cUL stranded hook-up wire

[Back to top](#)Standards and Regulations

Standards/specifications M12 connector In line with

Flame resistance in acc. to UL 1581 VW1

Halogen-free yes

Flammability rating according to UL 94 V0

Safety note WARNING: The connectors may not be plugge...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FSS-4P-M16/0,5PEMV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.