

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FST-4CON-M16/0,2 1497163 PHOENIX CONTACT Conect. plug. to be apar. wall poster., Power, 4-pole, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FST-4CON-M16/0,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FST-4CON-M16/0,2
Catalog number	1497163
Category	Circular connector, mounting (with cable)
Minimum order	100 Pcs
Document ID	EO-F1D1A3AD57
Generated	2026-08-05

Product Overview

Conect. plug. to be apar. wall poster., Power, 4-pole, Female connection, straight, M12-Standard, encoding: T, free cable end, Rear wall mounting, M16 x 1.5, Single stranded wires, cable length: 0.2 m, 1.31 mm², UL/cUL switching stranded wire
Connect. plug. for apar. poster wall., Rear mount
Device connector, rear mounting, Socket, straight, coding: T, on free cable end, Rear mounting, Individual wires

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesGeneral Lock nut is included in the scope of delivery
MountingMounting type Rear mounting
Connection method Individual wires
Product propertiesProduct type Circular connectors (device side)
Coding T
Thread type M12
Connection dataConductor connection
Connection method Individual wires
Contact connection type Socket
ConnectorConnection 1

Head design Socket
Head cable outlet straight
Coding T
Connection 2
Head design free cable end
ETIM for 1497163 Connectors (EC003570)
Feature Name
Feature Value
Cable length (EF000536)
0.2 mm
Type of plug-in contact, outer side (EF005528)
None
Mounting method (EF000003)
Back wall mounting
Housing material (EF001596)
Other
Material core insulation (EF000061)
Other
Material of contact surface (EF004020)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Ambient temperature (EF002386)
85 °C
Operating temperature (EF002393)
-25 °C
With shield connection (EF002535)
No
Screw-in thread (EF012303)
M12
Core cross section (EF000018)
1.31 mm²
Min. number of insertion cycles (EF012212)
100
Degree of protection (IP), mounted (EF007466)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FST-4CON-M16/0,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.