

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12MSL4FEM16XL-L180GRX 1239521 PHOENIX CONTACT Connect. plug. for apar. poster wall, Power, 5-pole,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12MSL4FEM16XL-L180GRX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12MSL4FEM16XL-L180GRX
Catalog number	1239521
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-58B951B12B
Generated	2026-08-05

Product Overview

Connect. plug. for apar. poster wall, Power, 5-pole, Male connector, straight, M12, encoding: L, Rear mount, M16 x 1.5, Soldering pins, RoHS II lead-free item without exception 6c (Pb< 0.1%)

Device connector, rear mounting, Power, 5-position, Pin, straight, M12, coding: L, Rear mounting, M16 x 1.5, Solder pins, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT
--------------	-----------------

Additional Product Information

Technical dataNotesGeneral The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

General FE not connected to metal parts that can be touched, no protective function

General Lock nut is included in the scope of delivery

MountingMounting type Rear mounting M16 x 1.5 With flat nut

Assembly instructions With flat nut

Connection method Solder pins

Product propertiesProduct type Circular connectors (device side)

Sensor type Power
Number of positions 5
Coding L
Thread type M12
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Material specifications Flammability rating according to UL 94 V0
Seal material FKM
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Material for screw connection Zinc die-cast, nickel-plated
Electrical properties Rated surge voltage 1.5 kV
Nominal voltage UN 63 V DC
Nominal current IN 16 A
Connection data Conductor connection
Connection method Solder pins
Contact connection type Pin
Mechanical properties Mechanical data
Insertion/withdrawal cycles > 100
Connector Connection 1
Head design Pin
Head cable outlet straight
Head thread type M12
Coding L
Cable/line Signal type/category Power
Environmental and real-life conditions Ambient con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12MSL4FEM16XL-L180GRX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.