

INDUSTRIAL COMPONENT DATA

SACC-DSI-M8FS-3CON-M12/3,0 PUR 1424316 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M8FS-3CON-M12/3,0 PUR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M8FS-3CON-M12/3,0 PUR
Catalog number	1424316
Category	Circular connector, mounting (with cable)
Minimum order	100 Pcs
Document ID	EO-12979D3593
Generated	2026-08-06

Product Overview

Flush-type connector

Built-in mounting female for sensors/actuators, 3 poles, M8, rear wall mounting/screwed with M12 thread, with 3 m PUR cable, 3 x 0.25 mm²

Sensor/actuator flush-type socket, 3-pos., M8, rear/screw mounting with M12 thread, with 3 m PUR cable, 3 x 0.25 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Technical dataMountingMounting type Rear mounting M12 x 1 With flat nut

Assembly note With flat nut

Product propertiesProduct type Circular connectors (device side)

Number of positions 3

No. of cable outlets 1

Shielded no

Coding A

Thread type M8

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Contact material Cu alloy
Contact surface material Au
Contact carrier material PUR/PA 6.6
Material for screw connection Brass, nickel-plated
Conductor material Tin-plated Cu litz wires
Electrical properties Rated surge voltage 1.5 kV
Contact resistance $\leq 3 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Connection data Conductor connection
Connection method Individual wires
Contact connection type Socket
Connector Connection 1
Head design Socket
Head cable outlet straight
Head thread type M8
Cable/line Cable length 3 m
Cable type PUR
Single wire, color brown, blue, black
Conductor material Tin-plated Cu litz wires
AWG signal line 24
Material wire insulation TPE
Environmental and real-life conditions Ambient conditions
Degree of protection IP67
IP67
Ambient temperature (operation) -25 °C ... 85 °C (Socket)
Standards and regulations Standard designation M8 connector
Standards/specifications IEC 61076-2-104
ETIM for 1424316 Connectors (EC002635)
Feature Name
Feature Value
Contact type (EF001587)
Other
Number of data contacts (EF012232)
0
Number of power contacts (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M8FS-3CON-M12/3,0 PUR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.