

INDUSTRIAL COMPONENT DATA

SACC-DSI-MSB-4CON-L180 SCO 1569618 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-MSB-4CON-L180 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-MSB-4CON-L180 SCO
Catalog number	1569618
Category	Circular connector, mounting (PCB)
Minimum order	60 Pcs
Document ID	EO-B2DE180C37
Generated	2026-08-05

Product Overview

Panel feed-through

Conect. plug. to be apar. poster wall, 4-pole, Male, straight, M12-SPEEDCON, coding: B, Rear mount, Pg9, Soldering pins, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240087

Rear-facing device connector, 4-pole, Male connector, straight, M12-SPEEDCONNEC, code: B, Rear-facing mounting, Pg9, Welding pins, Replacement product according to RoHS II without exception 6c (Pb < 0.1%) Reference: 1240087

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1569618

Packing unit 20 pc

Minimum order quantity 60 pc

Note Made to Order (non-returnable)

GTIN 4046356340458

Weight per Piece (excluding packing) 13.070 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length of the solder pin 6 mm

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding B - inverse

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder pins

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Nickel-plated brass

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC002061ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC
13.239121413

ETIM for 1569618 Connectors (EC003569)

Feature Name

Feature Value

Mounting method (EF000003)

Back wall mounting

Screw-in thread (EF012303)

PG9

With shield...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-MSB-4CON-L180 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.