

INDUSTRIAL COMPONENT DATA

SACC-DSIV-M12-PLUG-9 THR 1417984 PHOENIX CONTACT

Housing screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSIV-M12-PLUG-9 THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSIV-M12-PLUG-9 THR
Catalog number	1417984
Category	Housing for circular connectors
Minimum order	100 Pcs
Document ID	EO-8CCB623164
Generated	2026-08-05

Product Overview

Housing screw connection

Housing cable gland, Male connector, M12, Front mounting, M14 x 1, THR solder connection, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239180

Housing screw connection, Pin, M12, Rear mounting, M14 x 1, THR solder connection, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Order information: If necessary, order locking nut separately

Product propertiesProduct type Panel mounting base

Thread type M12

Data management status

Article revision 00

Connection dataConnection method THR solder connection

Tightening torque 2 ... 3 Nm

Material specificationsMaterial Brass, nickel-plated
Seal material FKM
FKM
Material for screw connection Brass, nickel-plated
ConnectorConnection 1
Head design Pin
Head thread type M12
Environmental and real-life conditionsAmbient conditions
Degree of protection (when plugged in) IP67 (correctly plugged in and locked)
Degree of protection IP67 (correctly plugged in and locked)
IP67, when in locked state
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
-40 °C ... 85 °C (without mechanical actuation)
Standards and regulationsM12
Standard designation M12 connector
Standards/specifications IEC 61076-2-101
Note In line with
MountingMounting type Rear mounting M14 x 1

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSIV-M12-PLUG-9 THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.