

**INDUSTRIAL COMPONENT DATA**

# SACC-E-FS-5CON-M16/0,26-0,5DO2 1416369 PHOENIX CONTACT Connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-FS-5CON-M16/0,26-0,5DO2



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | SACC-E-FS-5CON-M16/0,26-0,5DO2            |
| Catalog number  | 1416369                                   |
| Category        | Circular connector, mounting (with cable) |
| Minimum order   | 50 Pcs                                    |
| Document ID     | EO-66A167CD02                             |
| Generated       | 2026-08-03                                |

## Product Overview

### Connector

Conect. plug. to be apar. front wall, 5-pole, Connecting female, straight, M12, coding: A, free cable end, Front mounting, M16 x 1.5, Single stranded wires, cable length: 0.26 m, 0.50 mm²

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

## Additional Product Information

### Key Commercial Data

Orderkey 1416369

Packing unit 1

GTIN 4055626071640

Custom tariff number 85444290

### Dimensions

#### General

#### Standards and Regulations

#### Classifications

#### Ambient conditions

#### Connection data

#### Environmental Product Compliance

#### Dimensions

Fixed cable length 0.26

[Back to top](#)Ambient conditions

Ambient temperature (operation) -25 ... -85

[Back to top](#)General

Standards/regulations according to IEC 61076-2-101

Overvoltage category II

Mounting type Front wall/screw mounting

Coding A-coded

Thread type M16 x 1.5

Cable cross section 0.5

Rated surge voltage 1.5 kV AC

Degree of pollution 3

Degree of protection IP67

Number of positions 5

Current 4 A

Voltage 60 V

[Back to top](#)Connection data

Connection method Individual wires

[Back to top](#)Standards and Regulations

Standards/specifications according to IEC 61076-2-101

Safety note **WARNING:** The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- **WARNING:** Commission properly functioning products only. The products must be regularly inspected for damage.

Decommission defective products immediately. Replace damaged products. Repairs are not possible.

- **WARNING:** Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that o...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-FS-5CON-M16/0,26-0,5DO2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.