

INDUSTRIAL COMPONENT DATA

SACC-E-FSD-4CON-M16/0,5 PP 1027686 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-FSD-4CON-M16/0,5 PP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-FSD-4CON-M16/0,5 PP
Catalog number	1027686
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-81FEF94CF5
Generated	2026-08-01

Product Overview

Flush-type connector

Conect. plug. to be apar. front wall, PROFINET CAT5 (IEC11801:2002), 4-pole, Female built-in mount, straight, M12-Push-Pull, D, to free cable end, Front wall mounting, M16 x 1.5, Single stranded wires, cable length: 0.5 m, 0.34 mm², TPE braided wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1027686

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626533971

Weight per Piece (excluding packing) 23.500 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 0.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 1.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding D-coded

Standards/regulations M12 connector

Signal type/category Universal

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Front mounting M16 x 1.5

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material of grip body Nickel-plated brass

Material, knurls Nickel-plated brass

Material Brass, nickel-plated

Sealing material NBR/FKM

Additional material specifications PU 2K (Grout material)

Cable

Cable type TPE litz wire

Conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-FSD-4CON-M16/0,5 PP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.