


INDUSTRIAL COMPONENT DATA

SACC-E-FSD-4P-M16/0,5 SCO GN 1067227 PHOENIX CONTACT Bus system flat-type plug SACC-E-FSD-4P-M16/0,5 SCO GN ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-FSD-4P-M16/0,5 SCO GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-FSD-4P-M16/0,5 SCO GN
Catalog number	1067227
Category	Circular connector, mounting (with cable)
Minimum order	100 Pcs
Document ID	EO-41162E82C1
Generated	2026-08-02

Product Overview

Bus system flat-type plug - SACC-E-FSD-4P-M16/0,5 SCO GN - 1067227

Built-in mounting female for bus system, PROFINET, 4-pole, SPEEDCON M12, D-coded, front wall mount/M16 thread screw mount, with 0.5 m TPE braided thread, 4 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Bus system flush-type socket, PROFINET, 4-pos., M12-SPEEDCON, D-coded, front/screw mounting with M16 thread, with 0.5 m TPE litz wire, 4 x 0.34 mm²

Key Commercial Data

Orderkey 1067227

Packing unit 1

GTIN 4055626735962

Custom tariff number 85444290

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCI@ss

eCI@ss 8.0 27279218

eCI@ss 9.0 27440103

ETIM

ETIM 5.0 EC001855

ETIM 6.0 EC002061

ETIM for 1067227 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

0.5 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Front mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

250 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

0.34 mm²

Min. number of insertion cycles (EF012212)

100

Degree of protection (IP), mounted (EF007466)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-FSD-4P-M16/0,5 SCO GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.