

INDUSTRIAL COMPONENT DATA

SACC-E-M12FS-4CON-PG9/0,5 PO 1401076 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12FS-4CON-PG9/0,5 PO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12FS-4CON-PG9/0,5 PO
Catalog number	1401076
Category	Sensor-actuator connector chassis
Minimum order	100 Pcs
Document ID	EO-95FBE9E36C
Generated	2026-08-05

Product Overview

Panel feed-through

Built-in mounting female for sensors/actuators, 4-pole, M12, A-coded, front wall mount/screw mount with Pg9 thread, with 0.5 m TPE wire, 4 x 0.34 mm²
STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1401076

Packing unit 1 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356522304

Weight per Piece (excluding packing) 20.400 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 0.5 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA66 GF

Material, knurls Nickel-plated brass

Sealing material NBR

Cable

Cable type TPE litz wire

Conductor cross section 0.34 mm^2

AWG signal line 22

Conductor structure signal line $7 \times 0.25 \text{ mm}$ Core diameter including insulation $1.2 \text{ mm} \pm 0.07 \text{ mm}$ Thickness, insulation 0.21 mm

Wire colors brown, white, blue, black

Material conductor insulation TPE

Conductor material Tin-plated Cu litz wires

Standards/specifications M12 connector IEC 61076-2-101

Insulation resistance $\geq 20 \text{ M}\Omega \cdot \text{km}$ Conductor resistance $\leq 57.6 \text{ m}\Omega/\text{km}$

Nominal voltage, cable 300 V

Test voltage, cable 2000 V AC

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12FS-4CON-PG9/0,5 PO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.