

INDUSTRIAL COMPONENT DATA

SACC-E-M12FS-8CON-PG9/2,0 1401846 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12FS-8CON-PG9/2,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12FS-8CON-PG9/2,0
Catalog number	1401846
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-6E3D23A471
Generated	2026-08-05

Product Overview

Flush-type connector

Conect. plug. to be apar. front wall, Universal, 8-pole, Female connection, straight, M12, coding: A, Front wall mounting, cable length: 2 m, 0.25 mm², TPE braided wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1401846

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356574259

Weight per Piece (excluding packing) 65.300 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 2 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 2 A

Rated voltage 30 V

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Signal type/category Universal

Status display No

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA66 GF

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Cable

Cable type TPE litz wire

Conductor cross section 0.25 mm^2

AWG signal line 24

Conductor structure signal line $14 \times 0.15 \text{ mm}$ Core diameter including insulation $1.15 \text{ mm} \pm 0.07 \text{ mm}$ Thickness, insulation 0.21 mm

Wire colors Brown, blue, white, gray, pink, green, yellow, red

Material conductor insulation TPE

Conductor material Tin-plated Cu litz wires

Insulation resistance $\geq 20 \text{ M}\Omega \cdot \text{km}$ Conductor resistance $\leq 80 \text{ m}\Omega/\text{m}$

Nominal voltage, cable 300 V

Test voltage, cable 2000 V AC

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Cla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12FS-8CON-PG9/2,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.