

INDUSTRIAL COMPONENT DATA

SACC-E-M12FST-4CON-M16/3,0X 1239508 PHOENIX CONTACT Conect. plug. to be apar. front wall, Power, 4-pole, Fem..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12FST-4CON-M16/3,0X



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12FST-4CON-M16/3,0X
Catalog number	1239508
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-EE55C4F245
Generated	2026-08-05

Product Overview

Conect. plug. to be apar. front wall, Power, 4-pole, Female connection, straight, M12-Standard, coding: T, free cable end, Front mounting, M16 x 1.5, Single stranded wires, cable length: 3 m, 1.31 mm², UL/cUL switching twisted wire, The item is lead-free according to RoHS II without exception 6c (Pb<0.1%)

Incorp. mount plug-in connector, Power, 4-pole, Connecting female, M12, T - Power, Front wall mounting, Square flange, Individual braided wires, cable length: 3 m, 0.34 mm², UL/cUL switching braided wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

ETIM for 1239508 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

3 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Front mounting

Housing material (EF001596)
Other
Material core insulation (EF000061)
Other
Material of contact surface (EF004020)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Ambient temperature (EF002386)
85 °C
Operating temperature (EF002393)
-25 °C
Rated voltage (EF000228)
63 V
With shield connection (EF002535)
No
Screw-in thread (EF012303)
M12
Core cross section (EF000018)
1.31 mm²
Min. number of insertion cycles (EF012212)
100
Degree of protection (IP), mounted (EF007466)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12FST-4CON-M16/3,0X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.