

INDUSTRIAL COMPONENT DATA

SACC-E-M12MS-5CON-M16/1,0 1575550 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MS-5CON-M16/1,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MS-5CON-M16/1,0
Catalog number	1575550
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-237BA34C73
Generated	2026-08-05

Product Overview

Flush-type connector

Conect. plug. to be apar. front wall, 5-pole, Male connector, straight, M12, coding: A, to free cable end, Front mount, M16 x 1.5, TPE braided wire, M16 x 1.5 cable gland, TPE braided wire

Front wall headers, Universal, 5-pole, Male connector, straight, M12, code: A, free-end, Front mounting, M16 x 1.5, Individual cords, cable length: 1 m, cable gland M16 x 1.5, 0.25 mm², TPE cord

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1575550

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356434829

Weight per Piece (excluding packing) 27.200 g

Custom tariff number 85444290

Country of origin DE (Germany)

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC002061ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0131251501UNSPSC 7.090131251501UNSPSC 1131251501UNSPSC 12.0131251501UNSPSC
13.239121413

ETIM for 1575550 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

1 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Front mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

60 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

0.25 mm²

Degree of protection (IP), mounted (EF007466)

IP67

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MS-5CON-M16/1,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.