

INDUSTRIAL COMPONENT DATA

SACC-E-M12MS-5CON-PG9/0,115TIN 1563973 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MS-5CON-PG9/0,115TIN



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MS-5CON-PG9/0,115TIN
Catalog number	1563973
Category	Sensor-actuator connector chassis
Minimum order	100 Pcs
Document ID	EO-6EDA272C1A
Generated	2026-08-05

Product Overview

Panel feed-through

Built-in mounting plug for sensors/actuators, 5 poles, M12, A-coded, front wall mount/bolt-on mount with Pg9 thread, with 0.115 m TPE braided wire, 5 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1563973

Packing unit 1 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356304382

Weight per Piece (excluding packing) 12.800 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 0.115 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 5

Insulation resistance > 10 ?

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA66 GF

Material, knurls Nickel-plated brass

Sealing material NBR

Cable

Cable type TPE litz wire

Conductor cross section 0.34 mm²

AWG signal line 22

Conductor structure signal line 7x 0.25 mm

Core diameter including insulation 1.2 mm ±0.07 mm

Thickness, insulation 0.21 mm

Wire colors Black, brown, blue, white, gray

Material conductor insulation TPE

Conductor material Tin-plated Cu litz wires

Insulation resistance ≥ 20 M?·km

Conductor resistance ≤ 57.6 ?/km

Nominal voltage, cable 300 V

Test voltage, cable 2000 V AC

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.1271434...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MS-5CON-PG9/0,115TIN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.