

INDUSTRIAL COMPONENT DATA

SACC-E-M12MSL4FEM16XL/0,2GR-1,5X 1239541 PHOENIX CONTACT Conect. plug. to be apar. front wall, Power, 5-pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MSL4FEM16XL/0,2GR-1,5X



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MSL4FEM16XL/0,2GR-1,5X
Catalog number	1239541
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-EC89B94CCA
Generated	2026-08-06

Product Overview

Conect. plug. to be apar. front wall, Power, 5-pole, Male connector, straight, M12-Standard, coding: L, free cable end, Front mounting, M16 x 1.5, Single stranded wires, cable length: 0.2 m, 1.31 mm², UL/cUL switching twisted wire, The item does not contain lead according to the RoHS II directive without exception 6c (Pb<.; 0.1 %)

Incorp. mount plug-in connector, Power, 5-pole, Male connector, M12, L - Power, Front wall mounting, Square flange, Individual braided wires, cable length: 0.2 m, 1.31 mm², UL/cUL switching braided wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

ETIM for 1239541 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

0.2 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Front mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)
Other
Material of contact surface (EF004020)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Ambient temperature (EF002386)
85 °C
Operating temperature (EF002393)
-25 °C
With shield connection (EF002535)
No
Screw-in thread (EF012303)
M12
Core cross section (EF000018)
1.31 mm²
Min. number of insertion cycles (EF012212)
100
Degree of protection (IP), mounted (EF007466)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MSL4FEM16XL/0,2GR-1,5X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.