

## INDUSTRIAL COMPONENT DATA

**SACC-E-M12MSS-2PE-M16XL/2,0-US 1329912 PHOENIX CONTACT** Conect. plug. to be apar. front wall, Power, 3-pole,

..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MSS-2PE-M16XL/2,0-US



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | SACC-E-M12MSS-2PE-M16XL/2,0-US            |
| Catalog number  | 1329912                                   |
| Category        | Circular connector, mounting (with cable) |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-33D3619735                             |
| Generated       | 2026-08-03                                |

## Product Overview

Conect. plug. to be apar. front wall, Power, 3-pole, Built-in connector, straight, M12-Standard, encoding: S, to free cable end, Front mounting, M16 x 1.5, Single stranded wires, cable length: 2 m, 2.50 mm², PEX conductor

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

ETIM for 1329912 Connectors (EC002635)

Feature Name

Feature Value

Contact type (EF001587)

Other

Number of data contacts (EF012232)

0

Number of power contacts (EF012216)

0

Number of control contacts (EF012217)

3

Type of housing (EF006980)

Straight

Rated current I<sub>n</sub> (EF008250)

16 A

Ambient temperature (EF002386)

-25 °C

Over voltage category (EF006785)

III

Pollution degree (EF006786)

3

Material of contact surface (EF004020)

Nickel

Material thread ring (EF012304)

Other

Type of locking (EF000208)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

With protective conductor (EF007468)

No

Degree of protection (IP), mounted (EF007466)

IP65/IP67

Min. number of insertion cycles (EF012212)

100

Screened (EF000881)

No

With status indication (EF001602)

No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MSS-2PE-M16XL/2,0-US with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.