

INDUSTRIAL COMPONENT DATA

SACC-E-M12MSS-3P-M16/1,5 PE 1068167 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MSS-3P-M16/1,5 PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MSS-3P-M16/1,5 PE
Catalog number	1068167
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-0F3088DC58
Generated	2026-08-01

Product Overview

Flush-type connector

Conect. plug. to be apar. front wall, Power, 3-pole, Male connector, M12, coding: S, Front mounting, M16 x 1.5, Single stranded wires, PP thread, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1238249

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1068167

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626740508

Weight per Piece (excluding packing) 89.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 5.0EC002061ETIM 6.0EC002061

ETIM for 1068167 Connectors (EC003570)

Feature Name**Feature Value**

Cable length (EF000536)

1.5 mm

Mounting method (EF000003)

Front mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

60 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

1.31 mm²

Min. number of insertion cycles (EF012212)

100

Degree of protection (IP), mounted (EF007466)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MSS-3P-M16/1,5 PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.