

INDUSTRIAL COMPONENT DATA

SACC-FPF-F-M12/M16 SMD PPI 1454497 PHOENIX CONTACT M12 Push-Pull housing screwing for M12 female connector i..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-FPF-F-M12/M16 SMD PPI



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-FPF-F-M12/M16 SMD PPI
Catalog number	1454497
Category	Housing for circular connectors
Minimum order	20 Pcs
Document ID	EO-31BB979E66
Generated	2026-08-06

Product Overview

M12 Push-Pull housing screwing for M12 female connector inserts, with profiled gasket

M12 push-pull housing screw connection for M12 socket inserts, with molded seal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Technical dataNotesGeneral The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

General If necessary, order locking nut separately

Product propertiesProduct type Panel mounting base

Thread type M12

Connection dataConnection method SMD

Cross section AWG (converted acc. to IEC)

Material specificationsFlammability rating according to UL 94 V0

Material of grip body Brass, nickel-plated

Material for screw connection Brass, nickel-plated

ConnectorConnection 1

Head design Socket

Head thread type M12
Head locking type Push-Pull
Mechanical properties Mechanical data
Insertion/withdrawal cycles > 100
Environmental and real-life conditions Ambient conditions
Degree of protection (when plugged in) IP65/IP67 (correctly plugged in and locked)
Degree of protection IP65/IP67 (correctly plugged in and locked)
IP67, when in locked state
IP65, when in locked state
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
-40 °C ... 85 °C (without mechanical actuation)
Standards and regulations M12
Standard designation M12 connector
Standards/specifications IEC 61076-2-010
Note In line with
Mounting Mounting type M16
Connection method SMD

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-FPF-F-M12/M16 SMD PPI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.