

INDUSTRIAL COMPONENT DATA

SACCBP-FS-12CON-M16/2,0-PVCSCOX 1239766 PHOENIX CONTACT Conect. plug. to be apar. wall poster., Universal, 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-FS-12CON-M16/2,0-PVCSCOX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-FS-12CON-M16/2,0-PVCSCOX
Catalog number	1239766
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-CFE9998D94
Generated	2026-08-04

Product Overview

Conect. plug. to be apar. wall poster., Universal, 12-pole, PVC/PVC, black RAL 9005, shielded, Female connection, straight, M12-SPEEDCON, coding: A, free cable end, Rear wall mounting, M16 x 1.5, Cable connection, cable length: 2 m, 0.14 mm², black PVC, The item does not contain lead according to the RoHS II directive without exception 6c (Pb<.; 0.1 %)

Connect. Plug. to apar. poster wall, Universal, 12-pole, black RAL 9005, shielded, Built-in mounting female, straight, M12-SPEEDCON, A-coded, to free cable end, Single stranded wires, cable length: 2m, PVC black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

ETIM for 1239766 Connectors (EC002635)

Feature Name

Feature Value

Contact type (EF001587)

Other

Number of data contacts (EF012232)

0

Number of power contacts (EF012216)

0

Number of control contacts (EF012217)

12

Type of housing (EF006980)

Straight

Rated current I_n (EF008250)

1.5 A

Ambient temperature (EF002386)

-25 °C

Rated voltage (EF000228)

30 V

Over voltage category (EF006785)

II

Pollution degree (EF006786)

3

Material of contact surface (EF004020)

Gold

Housing material (EF001596)

Plastic

Material thread ring (EF012304)

Other

Type of locking (EF000208)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

With protective conductor (EF007468)

No

Degree of protection (IP), mounted (EF007466)

IP67

Min. number of insertion cycles (EF012212)

100

Screened (EF000881)

Yes

With status indication (EF001602)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-FS-12CON-M16/2,0-PVCSCOX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.