

**INDUSTRIAL COMPONENT DATA**

# SACCBP-FS-4CON-M16/2,0-PUR SCOX 1239246 PHOENIX CONTACT Conect. plug. to be apar. wall poster., Universal, 4..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-FS-4CON-M16/2,0-PUR SCOX



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | SACCBP-FS-4CON-M16/2,0-PUR SCOX           |
| Catalog number  | 1239246                                   |
| Category        | Circular connector, mounting (with cable) |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-3ACF53DBED                             |
| Generated       | 2026-08-04                                |

## Product Overview

Conect. plug. to be apar. wall poster., Universal, 4-pole, PUR, grayish black RAL 7021, Female connection, straight, M12-SPEEDCON, A-coding, free cable end, Cable connection, cable length: 2 m, halogen-free PUR black, The item does not contain lead according to the RoHS II directive without exception 6c (Pb< 0.1%)  
Built-in mount female, shielded, 4-pole, M12, A-coded, rear wall/screw mount with M16 thread, with 2 m cable, 4 x 0.34 mm<sup>2</sup>

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

ETIM for 1239246 Connectors (EC003570)  
Feature Name  
Feature Value  
Cable length (EF000536)  
2 mm  
Type of plug-in contact, outer side (EF005528)  
None  
Mounting method (EF000003)  
Back wall mounting  
Housing material (EF001596)  
Other  
Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

250 V

With shield connection (EF002535)

Yes

Screw-in thread (EF012303)

M12

Min. number of insertion cycles (EF012212)

100

Degree of protection (IP), mounted (EF007466)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-FS-4CON-M16/2,0-PUR SCOX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.