

INDUSTRIAL COMPONENT DATA

SACCBP-FS-4CON-M16/3,0-PUR SCO 1076052 PHOENIX CONTACT Flush-type connector

SACCBP-FS-4CON-M16/3,0-PUR SCO 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-FS-4CON-M16/3,0-PUR SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-FS-4CON-M16/3,0-PUR SCO
Catalog number	1076052
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-1556CDA0AB
Generated	2026-08-05

Product Overview

Flush-type connector - SACCBP-FS-4CON-M16/3,0-PUR SCO - 1076052

Built-in mount female, shielded, 4-pole, M12, A-coded, rear wall/screw mount with M16 thread, with 2 m cable, 4 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Flush-type socket, shielded, 4-pos., M12, A-coded, rear/screw mounting with M16 thread, with 2 m cable, 4 x 0.34 mm²

Key Commercial Data

Orderkey 1076052

Packing unit 1

GTIN 4055626783345

Custom tariff number 85444290

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCI@ss

eCI@ss 8.0 27440103
eCI@ss 9.0 27440102
ETIM
ETIM 5.0 EC002061
ETIM for 1076052 Connectors (EC002635)
Feature Name
Feature Value
Contact type (EF001587)
Other
Number of data contacts (EF012232)
0
Number of power contacts (EF012216)
0
Number of control contacts (EF012217)
4
Type of housing (EF006980)
Straight
Rated current In (EF008250)
4 A
Ambient temperature (EF002386)
-25 °C
Rated voltage (EF000228)
250 V
Over voltage category (EF006785)
II
Pollution degree (EF006786)
3
Material of contact surface (EF004020)
Gold
Housing material (EF001596)
Plastic
Material thread ring (EF012304)
Other
Type of locking (EF000208)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
With protective conductor (EF007468)
No
Degree of protection (IP), mounted (EF007466)
IP67
Min. number of insertion cycles (EF012212)
100
Screened (EF000881)
Yes
With status indication (EF001602)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-FS-4CON-M16/3,0-PUR SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.