

INDUSTRIAL COMPONENT DATA

SACCBP-MS-5CON-PG9/0,5-920SCOX 1239662 PHOENIX CONTACT Conect. plug. to be apar. wall poster., CANopen, Devi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-MS-5CON-PG9/0,5-920SCOX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-MS-5CON-PG9/0,5-920SCOX
Catalog number	1239662
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-04352AD234
Generated	2026-08-02

Product Overview

Conect. plug. to be apar. wall poster., CANopen, DeviceNet, 5-pole, halogen-free PUR, lilac red RAL 4001, shielded, Male connector, straight, M12-SPEEDCON, coding: A, at free cable end, Rear wall mounting, Cable connection, cable length: 0.5 m, CANopen/DeviceNet, PUR, violet, The item does not contain lead according to the RoHS II directive without exception 6c (Pb<.; 0.1 %)

Built-in mounting male for bus system, DeviceNet/CANopen, 5-pole, M12, shielded, A-coded, SPEEDCON, backwall mount/screwed mounting with Pg9 thread, with 1.0 m bus cable, 2 x 0.2 mm², 2 x 0.32 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

ETIM for 1239662 Connectors (EC002635)

Feature Name

Feature Value

Contact type (EF001587)

Other

Number of data contacts (EF012232)

0

Number of power contacts (EF012216)

0
Number of control contacts (EF012217)
5
Type of housing (EF006980)
Straight
Rated current In (EF008250)
4 A
Ambient temperature (EF002386)
-25 °C
Rated voltage (EF000228)
48 V
Over voltage category (EF006785)
II
Pollution degree (EF006786)
3
Material of contact surface (EF004020)
Nickel
Housing material (EF001596)
Plastic
Material thread ring (EF012304)
Other
Type of locking (EF000208)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
With protective conductor (EF007468)
No
Degree of protection (IP), mounted (EF007466)
IP67
Min. number of insertion cycles (EF012212)
100
Screened (EF000881)
Yes
With status indication (EF001602)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-MS-5CON-PG9/0,5-920SCOX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.