

## INDUSTRIAL COMPONENT DATA

# SACCEC-M12FS-5CON-M16/ 5,0-920X 1239896 PHOENIX CONTACT Conect. plug. to be apar. front wall, CANopen®, Devi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCEC-M12FS-5CON-M16/ 5,0-920X



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | SACCEC-M12FS-5CON-M16/ 5,0-920X           |
| Catalog number  | 1239896                                   |
| Category        | Circular connector, mounting (with cable) |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-4ADA179330                             |
| Generated       | 2026-08-05                                |

## Product Overview

Conect. plug. to be apar. front wall, CANopen®, DeviceNet™, 5-poles, halogen-free PUR, purple red RAL 4001, shielded, Female connection, straight, M12, A-coding, free cable end, Cable connection, cable length: 5 m, CANopen®/DeviceNet™, PUR, violet, The item does not contain lead according to the RoHS II directive without exception 6c (Pb< 0.1%)  
Built-in mounting female for bus system, DeviceNet/CANopen, 5-pole, M12, shielded, A-coded, front wall mount/screw-mounted with M16 thread, positionable, with 5 m bus cable, 2 x 0.2 mm², 2 x 0.32 mm²

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

ETIM for 1239896 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

5 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Front mounting

Housing material (EF001596)  
Other  
Material of contact surface (EF004020)  
Other  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Ambient temperature (EF002386)  
85 °C  
Operating temperature (EF002393)  
-25 °C  
Rated voltage (EF000228)  
48 V  
With shield connection (EF002535)  
Yes  
Screw-in thread (EF012303)  
M12  
Min. number of insertion cycles (EF012212)  
100  
Degree of protection (IP), mounted (EF007466)  
Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCEC-M12FS-5CON-M16/ 5,0-920X with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.