

INDUSTRIAL COMPONENT DATA

SACCEC-M12FSB-2CON-M16/4,0-910 1519820 PHOENIX CONTACT Bus system flat-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCEC-M12FSB-2CON-M16/4,0-910



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCEC-M12FSB-2CON-M16/4,0-910
Catalog number	1519820
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-F5D201141E
Generated	2026-08-05

Product Overview

Bus system flat-type plug

Built-in mounting female for bus system, PROFIBUS, 2-pole, M12, shielded, coded B, front wall mounting/screwed mounting with M16 thread, positionable, with 4 m bus cable, 2 x 0.25 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1519820

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4017918940294

Weight per Piece (excluding packing) 255.500 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 4 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A
Rated voltage 60 V
Number of positions 2
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding B - inverse
Status display No
Overvoltage category II
Degree of pollution 3
Test voltage 2500 V
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Material, knurls Metal
Cable
Cable type PROFIBUS
Conductor cross section 0.22 mm^2
AWG signal line 24
Conductor structure signal line $19 \times 0.12 \text{ mm}$
Core diameter including insulation $2.55 \text{ mm} \pm 0.07 \text{ mm}$
Wire colors Red, green
Type of pair shielding Aluminum-lined polyester foil
Overall twist 2 cores with 2 fillers to the core
Shielding Braided shielding made of galvanized copper wires
Optical shield covering 80 %
External sheath, color violet RAL 4001
External cable diameter 7.80 mm
Smallest bending radius, fixed installation min. 78 mm
Smallest bending radius, movable installation min. 78 mm
Number of bending cycles 5000000
Bending radius 78 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 7 m/s^2
Outer sheath, material PUR
Material conductor insulation Foamed PE
Conductor material Tin-plated Cu litz wires
Insulation resistance $\geq 5 \text{ G}\Omega \cdot \text{km}$
Conductor resistance $\leq 78.4 \text{ m}\Omega/\text{m}$
Worki...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCEC-M12FSB-2CON-M16/4,0-910 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.