

INDUSTRIAL COMPONENT DATA

PSR-MC34-3NO-1DO-24DC-SP 2700548 PHOENIX CONTACT

Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-MC34-3NO-1DO-24DC-SP



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-MC34-3NO-1DO-24DC-SP
Catalog number	2700548
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-ADCA7F7483
Generated	2026-08-06

Product Overview

Safety relays

Safety relay for emergency stop and safety doors up to SIL 3, cat. 4, PL e, 1 or 2 channel service, automatic or manual controlled start, short circuit detection, 3 trip circuits, US = 24 V DC, plug-in push-in terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2700548

Packing unit 1 pc

Catalog page Page 254 (C-6-2017)

GTIN 4046356912686

Weight per Piece (excluding packing) 173.700 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 12.5 mm

Height 116.6 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 55 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Power supply

Rated control circuit supply voltage US 24 V DC -15 % / +10 %

20.4 V DC ... 26.4 V DC

Rated control supply current IS typ. 84 mA

Power consumption at US typ. 2 W

Inrush current 5 A ($\tau = 200 \mu s$ at Us)

Filter time 1 ms (at A1 in the event of voltage dips at Us)

Protective circuit Surge protection Suppressor diode

Protection against polarity reversal for rated control circuit supply voltage

Digital inputs

Input voltage range "0" signal 0 V DC ... 5 V DC (for safe Off; at S12)

Input current range "0" signal 0 mA ... 2 mA (for safe Off; at S12)

Inrush current < 20 mA (with Us/Ixto S12)

< 200 mA (with Us/Ixto S34)

< 5 mA (with Us/Ixto S22)

> -15 mA (with Us/Ixto S22/0V)

Current consumption < 5 mA (with Us/Ixto S12)

< 5 mA....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-MC34-3NO-1DO-24DC-SP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.