

INDUSTRIAL COMPONENT DATA

PSR-SCP-230AC/ESAM2/3X1/1X2/B 2901430 PHOENIX CONTACT Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCP-230AC/ESAM2/3X1/1X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCP-230AC/ESAM2/3X1/1X2/B
Catalog number	2901430
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-DE875EB43D
Generated	2026-08-03

Product Overview

Safety relays

Safety relay for emergency stop control and protection door up to SIL 1, SIL CL 1, Cat. 1, PL c, depending on the application up to SIL 3, SIL CL 3, Cat. 4, PL e, single-channel operation, 3 trip circuits, nominal input voltage 230 V AC/DC, plug-in screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2901430

Packing unit 1 pc

Catalog page Page 260 (C-6-2017)

GTIN 4046356592185

Weight per Piece (excluding packing) 23.000 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Width 22.5 mm

Height 99 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US

Nominal input voltage UN 230 V AC

Input voltage range in reference to UN 0.85 ... 1.1

Typical input current at UN 22 mA

Voltage at input/start and feedback circuit ~ 24 V DC

Typical response time 50 ms (manual start)

300 ms (automatic start)

Typ. starting time with Us 300 ms (when controlled via A1 or S11/S12)

Typical release time 20 ms (when controlled via S11/S12)

150 ms (when controlled via A1)

Recovery time 1 s

Operating voltage display Green LED

Status display 2 x green LEDs

Protective circuit Surge protection Suppressor diode

Surge protection Varistor

Maximum switching frequency 0.5 Hz

Max. permissible overall conductor resistance 50 Ω

Output data

Contact type 3 enabling current paths

1 signaling current path

Contact material AgSnO₂, gold-flashed

Maximum switching vol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCP-230AC/ESAM2/3X1/1X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.