

INDUSTRIAL COMPONENT DATA

PSR-SCP-230UC/ESAM4/3X1/1X2/B 2901428 PHOENIX CONTACT Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCP-230UC/ESAM4/3X1/1X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCP-230UC/ESAM4/3X1/1X2/B
Catalog number	2901428
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-094596FE51
Generated	2026-08-03

Product Overview

Safety relays

Safety relay for emergency stop control and protection door up to SIL 3 or cat. 4, PL e according to EN ISO 13849, single or two channels, 3 trip circuits, nominal input voltage 230 V AC/DC, plug-in screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Safety**

Additional Product Information

Key Commercial Data

Orderkey 2901428

Packing unit 1 pc

Catalog page Page 260 (C-6-2017)

GTIN 4046356592062

Weight per Piece (excluding packing) 236.900 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Width 22.5 mm

Height 99 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US

Nominal input voltage UN 230 V AC/DC

Input voltage range in reference to UN 0.85 ... 1.1

Typical input current at UN 22 mA

Voltage at input/start and feedback circuit ~ 24 V DC

Typical response time 40 ms (man. start)

Typ. starting time with Us 330 ms (when controlled via A1)

Typical release time 150 ms (when controlled via A1)

20 ms (when controlled via S11/S12 and S21/S22)

Concurrence input 1/2 ?

Recovery time 1 s

Operating voltage display Green LED

Status display Green LED

Protective circuit Surge protection Varistor 275 VRMS(A1-A2)

Surge protection Varistor

Maximum switching frequency 0.5 Hz

Max. permissible overall conductor resistance 50 ?

Output data

Contact type 3 enabling current paths

1 signaling current path

Contact material AgSnO₂, + 0.2 μm Au

Maximum switching...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCP-230UC/ESAM4/3X1/1X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.