

INDUSTRIAL COMPONENT DATA

PSR-SCP- 24UC/URM/3X1/3X2 2981839 PHOENIX CONTACT

Coupling relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCP-24UC/URM/3X1/3X2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCP-24UC/URM/3X1/3X2
Catalog number	2981839
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-E98A0D7D0B
Generated	2026-08-03

Product Overview

Coupling relay

Safe coupling relay with forced-conduction contacts, 3 normally open contacts, 3 normally closed contacts, plug-in screw terminal, width: 22.5 mm

Safe coupling relay with force-guided contacts, 3 N/O contacts, 3 N/C contacts, plug-in screw terminal block, width: 22.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2981839

Packing unit 1 pc

Catalog page Page 278 (C-6-2017)

GTIN 4046356138604

Weight per Piece (excluding packing) 126.900 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 22.5 mm

Height 114.5 mm

Depth 99 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude max. 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US 24 V AC/DC -15 % / +10 %

Rated control supply current IS typ. 45 mA

Power consumption at US typ. 1.08 W

Inrush current typ. 350 mA DC (?t s)

typ. 350 mA AC (?t = 2 ms at Us)

Typ. starting time with Us typ. 15 ms (when controlled via A1)

Typical release time typ. 15 ms (when controlled via A1)

Recovery time < 500 ms

Operating voltage display 1 x green LED

Protective circuit Surge protection Suppressor diode

Maximum switching frequency 0.5 Hz

Output data

Contact type 3 enabling current paths

3 confirmation current paths

Contact material AgSnO2

Maximum switching voltage 230 V AC/DC (Observe the load curve)

Minimum switching voltage 5 V AC/DC

Limiting continuous current 6 A (N/O contact)

3 A (N/C contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCP-24UC/URM/3X1/3X2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.