

## INDUSTRIAL COMPONENT DATA

# SAMPLE PTSM 0,5/ 8-2,5-H-THR 1701099 PHOENIX CONTACT

## Sample set

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAMPLE PTSM 0,5/ 8-2,5-H-THR



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SAMPLE PTSM 0,5/ 8-2,5-H-THR   |
| Catalog number  | 1701099                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 5 Pcs                          |
| Document ID     | EO-02376B3EF4                  |
| Generated       | 2026-08-03                     |

## Product Overview

### Sample set

Terminal block for printed circuit board, nominal current: 6 A, nominal voltage (III/2): 160 V, nominal section: 0.5 mm<sup>2</sup>, number of potentials: 8, number of rows: 1, number of poles per row: 8, article family: PTSM 0.5/.. -H-THR, pitch: 2.5 mm, connection type: Push-in spring connection, mounting: Weld THR, conductor connection direction/printed circuit board: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.1 mm, number of solder pins per potential: 2, packaging type: boxed packaging. SAMPLE set with 5 items on strap. For use in a welding process, use the item without the SAMPLE identification

PCB terminal, Rated current: 6 A, Rated voltage (III/2): 160 V, Nominal cross-section: 0.5 mm<sup>2</sup>, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, Article family: PTSM 0.5/.. -H-THR, Pitch: 2.5mm, Connection Type: Push-in Spring Connector, Mounting: THR Soldering/Wave Soldering, Conductor/Board Connection Direction: 0°, Color: Black, Pin Layout: Linear Pinning, Pin Length [P]: 2.1mm, Number of Solder Pins Per Potential: 2, Packaging Type: Packed in Carton. SAMPLE set with 5 items in the belt section. For use in the soldering process, please use the articles without SAMPLE marking

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

### Key Commercial Data

Orderkey 1701099

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

GTIN 4046356515030

Weight per Piece (excluding packing) 2.230 g

Custom tariff number 85369010

Country of origin IN (India)

Dimensions

Length [ l ] 10 mm

Pitch 2.5 mm

Dimension a 17.5 mm

Width [ w ] 20.5 mm

Height 5 mm

Height [ h ] 7.1 mm

Solder pin [P] 2.1 mm

Pin spacing 2.5 mm

Hole diameter 1.2 mm

General

Range of articles PTSM 0,5/..-H-THR

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 63 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 200 V

Connection in acc. with standard EN-VDE

Nominal current IN 6 A

Nominal cross section 0.5 mm<sup>2</sup>

Maximum load current 6 A

Insulating material LCP

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 6 mm

Number of positions 8

Connection data

Conductor cross section solid min. 0.14 mm<sup>2</sup>

Conductor cross section solid max. 0.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 0.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.34 mm<sup>2</sup>

Conductor cross section AWG min. 26

Conductor cr...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAMPLE PTSM 0,5/ 8-2,5-H-THR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.