

INDUSTRIAL COMPONENT DATA

MC 1,5/ 2-STF-3,81 BD:-,+ 1705490 PHOENIX CONTACT

Plug-in part, rated current: 8 A, number of poles: 2, pitc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 2-STF-3,81 BD:-,+



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 2-STF-3,81 BD:-,+
Catalog number	1705490
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-87992D83A4
Generated	2026-08-05

Product Overview

Plug-in part, rated current: 8 A, number of poles: 2, pitch: 3.81 mm, connection type: Screw connection with traction capsule, color: green, contact surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Tin, contact type: Female connection, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MC 1.5/.. -STF, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, number of solder pins per potential: 1, plug-in system: MINI COMBICON, Locking: Screw lock, fixing type: Air clamping (screw), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Plug component, nominal current: 8 A, number of positions: 2, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin

Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsScrewable flange for superior mechanical stabilityKey Commercial Data

Orderkey 1705490

Packing unit 1

GTIN 4046356770521

Custom tariff number 85366990

General

Range of articles MC 1,5/...-STF

Type of contact Female connector

Number of positions 2

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.08 mm²

2 conductors with same cross section, solid max. 0.5 mm²

2 conductors with same cross section, st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 2-STF-3,81 BD:-,+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.