

INDUSTRIAL COMPONENT DATA

SB-8EPSA8AWT00S 1623375 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: SB-8EPSA8AWT00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	SB-8EPSA8AWT00S
Catalog number	1623375
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-E2A0BD90F3
Generated	2026-08-03

Product Overview

Device connector, front mounting

M40, Conect. plug. to be apar. front wall, SB, straight, shielded: yes, for standard and SPEEDCON lock, No. of poles: 8+4+PE, Direction of rotation: Standard, type of contact: Male, Crimped connection, Axial O-ring, 4x Ø4.2, flange measurement: 40 mm x 40 mm, coding:Signal, coding 1, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1244888

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1623375

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 128 (C-2-2017)

GTIN 4055626195155

Weight per Piece (excluding packing) 202.600 g

Custom tariff number 85366990

Country of origin DE (Germany)

Temperature range

Ambient temperature (operation) -40 °C ... 130 °C

Data of the insulating body

Coding Signal, coding 1

Contact connection method Crimp connection

Type of contacts Pin

Application Hybrid

Number of positions 13

Contact diameter of power contacts 3.6 mm

Litz wire cross section of power contacts min. 1 mm²

Litz wire cross section of power contacts max. 16 mm²

Nominal current per power contact at 25°C 70 A

Rated surge voltage 6 kV

Degree of pollution 3

Rated voltage (II/3) power contact 850 V DC

Rated voltage (III/3) power contact 630 V_~AC

Contact diameter of signal contacts 1 mm

Litz wire cross section of signal contacts min. 0.06 mm²

Litz wire cross section of signal contacts max. 1.5 mm²

Nominal current per signal contact at 25°C 8 A

Rated surge voltage 6 kV

Rated voltage (III/3) signal contact 500 V

Contact diameter, data contacts 1 mm

Litz wire cross section, data contacts, min. 0.06 mm²

Litz wire cross section, data contacts, max. 1.5 mm²

Nominal current per data contact at 25°C 8 A

Nominal voltage of data contact 50 V

Rated surge voltage 1.5 kV

Rated voltage (III/3) data contact 50 V

Housing data

Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Flange dimensions 40 mm x 40....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SB-8EPSA8AWT00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.