

INDUSTRIAL COMPONENT DATA

CT-TERMIBLOCK 10 DA 0441711 PHOENIX CONTACT Screw termination block

Brand: PHOENIX CONTACT | Manufacturer Part Number: CT-TERMIBLOCK 10 DA



Manufacturer	PHOENIX CONTACT
MPN / Reference	CT-TERMIBLOCK 10 DA
Catalog number	0441711
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-9209969603
Generated	2026-07-29

Product Overview

Screw termination block

Block of screw connection terminals with separation contacts for the reception of CT and CTM plug-in protections. Use in MSR and telecommunication systems. Execution: 10 two-wire circuits

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0441711

Packing unit 10 pc

Catalog page Page 169 (C-4-2017)

GTIN 4017918002213

Weight per Piece (excluding packing) 167.600 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Height 43 mm

Width 118 mm

Depth 40.9 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Altitude 2000 m

Degree of protection IP20

General

Housing material PA

Flammability rating according to UL 94 V2

Color black

Standards for clearances and creepage distances IEC 60664-1

Overvoltage category III

Degree of pollution 3

Mounting type DIN rail: 35 mm

Type LSA-PLUS module

Protective circuit

Maximum continuous voltage UC 240 V AC

Operating effective current ICat UC 5 A

Connection data

Connection method Screw terminal blocks

Connection method IN Screw terminal blocks

Connection method OUT Screw terminal blocks

Screw thread M3

Tightening torque 0.5 Nm

Stripping length 7 mm

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Environmental Product Compliance

REACH SVHC 4-Nonylphenol, ethoxylated

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0 27140201 eCl@ss 4.1 27130801 eCl@ss 5.0 27130801 eCl@ss 5.1 27130800 eCl@ss 6.0 27130800 eCl@ss 7.0 27130807 eCl@ss 8.0 27139202 eCl@ss 9.0 27130815

ETIM 2.0 EC000943 ETIM 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CT-TERMBLOCK 10 DA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.