

INDUSTRIAL COMPONENT DATA

CES-B24-HFFS-PLBK 0801661 PHOENIX CONTACT Sealing frame

Brand: PHOENIX CONTACT | Manufacturer Part Number: CES-B24-HFFS-PLBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	CES-B24-HFFS-PLBK
Catalog number	0801661
Category	Gland plate for small distribution boards/switchgear cabinets
Minimum order	1 Pcs
Document ID	EO-E66117CB71
Generated	2026-08-02

Product Overview

Sealing frame

Sealing frames, with locking flange, construction: B24, Number of cable seals (small): 10, material: PA (halogen-free), color: black, length: 147 mm, width: 58 mm, height: 20 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 0801661

Packing unit 1 pc

Catalog page Page 684 (C-2-2017)

GTIN 4046356674119

Weight per Piece (excluding packing) 171.000 g

Custom tariff number 85472000

Country of origin PL (Poland)

Dimensions

Length 147 mm

Width 58 mm

Height 20 mm

Ambient conditions

Degree of protection IP54

Ambient temperature (operation) -40 °C ... 120 °C (static)

General

Frame type Sealing frame

Material PA (halogen-free)

Flammability rating according to UL 94 V0

Color black

Torque 1.8 Nm (Mounting screw, M4 (ISO 4762/DIN 912))

Note Mounting screws not supplied as standard. The maximum width of the panel cutout must not exceed 51 mm (instead of 35 mm for heavy-duty industrial connectors).

Installation instructions One large sleeve requires the space of 4 small sleeves, M4 mounting screws (ISO 4762/DIN 912), torque for mounting screw: 1.8 Nm

A video tutorial on how to assemble the product can be found in the Downloads area, in the Video category.

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0 23110102 eCl@ss 4.1 23110102 eCl@ss 5.0 23110102 eCl@ss 5.1 23110100 eCl@ss 6.0 23110100 eCl@ss 7.0 27142421 eCl@ss 8.0 27142421 eCl@ss 9.0 27142421

ETIM 3.0 EC001121 ETIM 4.0 EC002498 ETIM 5.0 EC000211 ETIM 6.0 EC000211

UNSPSC 6.01 27113201 UNSPSC 7.0901 27...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CES-B24-HFFS-PLBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.