

INDUSTRIAL COMPONENT DATA

CES-B16-SFFS-PLBK 0801659 PHOENIX CONTACT Sealing frame

Brand: PHOENIX CONTACT | Manufacturer Part Number: CES-B16-SFFS-PLBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	CES-B16-SFFS-PLBK
Catalog number	0801659
Category	Gland plate for small distribution boards/switchgear cabinets
Minimum order	1 Pcs
Document ID	EO-F3D76AD98D
Generated	2026-08-02

Product Overview

Sealing frame

Sealing frames, with screw lock, construction: B16, Number of cable seals (small): 8, material: PA (halogen-free), color: black, length: 120 mm, width: 58 mm, height: 20 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 0801659

Packing unit 1 pc

Catalog page Page 685 (C-2-2017)

GTIN 4046356674133

Weight per Piece (excluding packing) 146.700 g

Custom tariff number 85472000

Country of origin PL (Poland)

Dimensions

Length 120 mm

Width 58 mm

Height 20 mm

Ambient conditions

Degree of protection IP54

IP65

Ambient temperature (operation) -40 °C ... 120 °C (static)

General

Frame type Sealing frame

Material PA (halogen-free)

Flammability rating according to UL 94 V0

Color black

Torque 2 Nm ... 4 Nm (Locking screw)

Note Mounting screws not supplied as standard. The maximum width of the panel cutout must not exceed 51 mm (instead of 35 mm for heavy-duty industrial connectors).

Installation instructions M4 locking screw with 3 mm Allen screw head, 3 ... 4 Nm torque, 1 large sleeve requires the space of 4 small sleeves, mounting screw: M4 (ISO 4762/DIN 912), 1.8 Nm torque

The flat gasket supplied should be inserted between the wall and the sealing frame in the case of wall mounting. IP54: for vertical sealing frame mounting/for horizontal sealing frame mounting (downward cable outlet direction). IP65: when using the CES-SRC-BK / CES-LRC-BK cone sleeve, for vertical mounting/horizontal mounting (downward cable outlet direction) of the sealing frame directly on the housing panel, and use of a 3.6 mm wide cable binder (e.g., item 3240744).

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

Ch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CES-B16-SFFS-PLBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.