

INDUSTRIAL COMPONENT DATA

VS-PPC-C2-PC-ROBK-L 1405303 PHOENIX CONTACT

Protective covers

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-C2-PC-ROBK-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-C2-PC-ROBK-L
Catalog number	1405303
Category	Cap for industrial connectors
Minimum order	1 Pcs
Document ID	EO-7C1517B2C3
Generated	2026-08-02

Product Overview

Protective covers

Locking sealing plug for Push-Pull Power recessed frame (VS-PPC-F2...), IP65 rating

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1405303

Packing unit 1 pc

Catalog page Page 368 (C-2-2017)

GTIN 4046356420419

Weight per Piece (excluding packing) 9.900 g

Custom tariff number 39269097

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -5 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

General data

Degree of pollution 2

Alternative short product description Sealing plug for panel mounting frame

Locking type Push Pull

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027261200eCl@ss

7.027440208eCl@ss 8.027440208eCl@ss 9.027440208

ETIM 3.0EC000723ETIM 4.0EC002314ETIM 5.0EC002314ETIM 6.0EC002314

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.239121421

ETIM for 1405303 Connectors (EC002314)

Feature Name

Feature Value

Type of locking (EF000208)

Push Pull

With sealing (EF005610)

No

With captivity element (EF012222)

No

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-C2-PC-ROBK-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.