

INDUSTRIAL COMPONENT DATA

STTB 2,5/2P-FS 3061428 PHOENIX CONTACT Self-locking flange

Brand: PHOENIX CONTACT | Manufacturer Part Number: STTB 2,5/2P-FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	STTB 2,5/2P-FS
Catalog number	3061428
Category	End bracket for terminal block
Minimum order	50 Pcs
Document ID	EO-F8AA27F1A4
Generated	2026-08-03

Product Overview

Self-locking flange

Lace flange, mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3061428

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 369 (C-1-2017)

GTIN 4046356555067

Weight per Piece (excluding packing) 5.830 g

Custom tariff number 39269097

Country of origin PL (Poland)

General

Number of levels 2

Color gray

Insulating material PA

Flammability rating according to UL 94 V0
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Dimensions
Width 5.2 mm
End cover width 2.2 mm
Length 71.5 mm
Height 40 mm
Height NS 35/7,5 47.5 mm
Height NS 35/15 55 mm
Standards and Regulations
Flammability rating according to UL 94 V0
Fire protection for rail vehicl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STTB 2,5/2P-FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.