

INDUSTRIAL COMPONENT DATA

SACB-10/3-L-M16-M8 1516218 PHOENIX CONTACT

Sensor/actuator box

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-10/3-L-M16-M8



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-10/3-L-M16-M8
Catalog number	1516218
Category	Passive sensor-actuator interface (with cable)
Minimum order	1 Pcs
Document ID	EO-97702FF4AB
Generated	2026-07-29

Product Overview

Sensor/actuator box

Sensor/actuator box, application: Standard, connection type: Female M8 Metal, number of plug-in stations: 10, number of poles: 3, occupancy of plug-in stations: single, status indication: Yes, pnp; Main cable connection: M16 90° plug-in connection, shielding: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1516218

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 267 (C-2-2017)

GTIN 4017918967147

Weight per Piece (excluding packing) 164.700 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Rated voltage 24 V DC

Max. operating voltage Umax 30 V DC

Current carrying capacity per I/O signal 2 A
Current carrying capacity per slot 2 A
Total rated current 6 A
Number of positions 3
Number of slots 10
Flammability rating according to UL 94 V0
Sensor/actuator connection system M8 socket
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -30 °C ... 80 °C
Local diagnostics function
Local diagnostics Supply voltage per module Green LED
Status display I/O Yellow LED
Master cable data/connection data
Connection method M16 plug connection
Tightening torque - master cable - plug connection 1.5 Nm
Tightening torque slot sensor/actuator cable 0.2 Nm
Insulation material
Housing material PBT
Material of the moulding mass PUR
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of contact, master cable side CU alloy
Material of threaded sleeve Cu alloy
Material of threaded sleeve surface Nickel-plated
O-ring material NBR
Pin assignment
Slot/position = Wire color or connection 1 / 4 (A) = P
2 / 4 (A) = J
3 / 4 (A) = T
4 / 4 (A) = S
5 / 4 (A) = G
6 / 4 (A) = R
7 / 4 (A) = E
8 / 4 (A) = O
9 / 4 (A) = C
10 / 4 (A) = N
1-10 / 1 (+24 V) = A+M
1-10 / 3 (0 V) = L+U
Stan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-10/3-L-M16-M8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.