

## INDUSTRIAL COMPONENT DATA

# SACB- 4/4-L-C QO-0,34 1548383 PHOENIX CONTACT

## Sensor/actuator box

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB- 4/4-L-C QO-0,34



|                 |                                                |
|-----------------|------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                |
| MPN / Reference | SACB- 4/4-L-C QO-0,34                          |
| Catalog number  | 1548383                                        |
| Category        | Passive sensor-actuator interface (with cable) |
| Minimum order   | 1 Pcs                                          |
| Document ID     | EO-9B23EF62ED                                  |
| Generated       | 2026-08-03                                     |

### Product Overview

Sensor/actuator box

Sensor/Actuator Box, Application: Standard, Connection Type: QUICKON, 0.14 mm<sup>2</sup> ... 0.34 mm<sup>2</sup>, number of plug-in stations: 4, number of poles: 4, occupancy of plug-in stations: Double, status indication: Yes, pnp; Main cable connection: 180° plug-in screw connection, shielding: No

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; QUICKON Installation System (QPD)

### Additional Product Information

Key Commercial Data

Orderkey 1548383

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 272 (C-2-2017)

GTIN 4046356142854

Weight per Piece (excluding packing) 209.760 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Rated voltage 24 V DC

Max. operating voltage U<sub>max</sub> 30 V DC

Current carrying capacity per I/O signal 2 A  
Current carrying capacity per slot 4 A  
Total rated current 10 A  
2x 8 A (For electrical isolation)  
Number of positions 4  
Number of slots 4  
Flammability rating according to UL 94 V0  
Sensor/actuator connection system QUICKON  
Ambient conditions  
Degree of protection IP65  
IP67  
IP69K  
Ambient temperature (operation) -30 °C ... 80 °C  
Local diagnostics function  
Local diagnostics Supply voltage per module Green LED  
Status display I/O Yellow LED  
Master cable data/connection data  
Connection method Pluggable screw connection  
Conductor cross section min. (signal) 0.14 mm<sup>2</sup>  
Conductor cross section max. (signal) 1.5 mm<sup>2</sup>  
Conductor cross section AWG min. (signal) 26  
Conductor cross section AWG max. (signal) 16  
Stripping length (signal) 7 mm  
Conductor cross section min. (energy) 0.14 mm<sup>2</sup>  
Conductor cross section max. (energy) 1.5 mm<sup>2</sup>  
Conductor cross section AWG min. (energy) 26  
Conductor cross section AWG max. (energy) 16  
External cable diameter min. 7 mm  
External cable diameter max. 12 mm  
Stripping length 50 mm (Master cable)  
Tightening torque, cover screw 0.35 Nm  
Tightening torque, union nut 2.5 Nm  
Tightening torque of mounting screw for fi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB- 4/4-L-C QO-0,34 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.