

INDUSTRIAL COMPONENT DATA

SACB- 6/3-C QO-0,34 1548367 PHOENIX CONTACT

Sensor/actuator box

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB- 6/3-C QO-0,34



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB- 6/3-C QO-0,34
Catalog number	1548367
Category	Passive sensor-actuator interface (with cable)
Minimum order	1 Pcs
Document ID	EO-B2EF2E9C00
Generated	2026-07-31

Product Overview

Sensor/actuator box

Sensor/Actuator Box, Application: Standard, Connection Type: QUICKON, 0.14 mm² ... 0.34 mm², number of plug-in workstations: 6, number of poles: 3, occupation of plug-in workstations: single, status indication: No, Universal; Main cable connection: 180° plug-in screw connection, shielding: No

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1548367

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 272 (C-2-2017)

GTIN 4046356142830

Weight per Piece (excluding packing) 267.620 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Rated voltage 48 V

60 V DC

Current carrying capacity per I/O signal 2 A
Current carrying capacity per slot 4 A
Total rated current 10 A
2x 8 A (For electrical isolation)
Number of positions 3
Number of slots 6
Flammability rating according to UL 94 V0
Sensor/actuator connection system QUICKON
Ambient conditions
Degree of protection IP65
IP67
IP69K
Ambient temperature (operation) -30 °C ... 80 °C
Master cable data/connection data
Connection method Pluggable screw connection
Conductor cross section min. (signal) 0.14 mm²
Conductor cross section max. (signal) 1.5 mm²
Conductor cross section AWG min. (signal) 26
Conductor cross section AWG max. (signal) 16
Stripping length (signal) 7 mm
Conductor cross section min. (energy) 0.14 mm²
Conductor cross section max. (energy) 1.5 mm²
Conductor cross section AWG min. (energy) 26
Conductor cross section AWG max. (energy) 16
External cable diameter min. 7 mm
External cable diameter max. 12 mm
Stripping length 50 mm (Master cable)
Tightening torque, cover screw 0.35 Nm
Tightening torque, union nut 2.5 Nm
Tightening torque of mounting screw for fixing the housing 0.5 Nm
Conductor data
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter Class 2-6
Wire insulation m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB- 6/3-C QO-0,34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.