

INDUSTRIAL COMPONENT DATA

SAC-3P-10,0-PUR/A-1L-R-ES 1413118 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-10,0-PUR/A-1L-R-ES



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-10,0-PUR/A-1L-R-ES
Catalog number	1413118
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-000BB77C9D
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 3-pole, free cable end, to Valve Connectors A, with 1 LED, connected to Free Flow Diode with Hold Current Limiter, Cable Length: 10 m, with Hold Current Limiter for Energy Reduction

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Valve connector A, with 1 LED, Wiring: Freewheeling diode with holding current limiting device, cable length: 10 m, with holding current limiting device for energy reduction

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable with valve connector

Application Standard

Number of positions 3

No. of cable outlets 1

Shielded no

Data management status

Article revision 01

Material specificationsSeal material TPU

Material housing valve plug TPU

Contact material CuSn

Valve plug contact insert material PA 6.6
Contact surface material Ag
Electrical properties Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 24 V DC $\pm 20 \%$
Nominal current IN 1 A
Valve connector characteristics
Switch-over time approx. 200 ms (Initial operating time)
Clock frequency approx. 2500 Hz (Holding current limiting device)
Switching frequency max. 5 Hz (Connected valve)
Fixing screws M3 x 28
Signaling Status display 1 LED
Status display present Yes
Connector Connection 1
Type free cable end
Connection 2
Type Valve connector A
Number of positions 3
Material CuSn (Contact)
Ag (Contact surface)
PBT (Contact carriers)
TPU (Housing)
Cable/line Cable length 10 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 30 kg/km
UL AWM Style 20549
Number of positions 3
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 28x 0.15 mm
AWG signal line 20
Conductor cross section 3x 0.5 mm²
Wire diameter incl. insulation 1.5 mm $\pm 0.05 \text{ mm}$ (Signal line)
External cable diameter 4.50 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color black 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-10,0-PUR/A-1L-R-ES with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.