

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 5,0-PVC 1415589 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 5,0-PVC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 5,0-PVC
Catalog number	1415589
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-FA6FA3A9B0
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, PVC, black RAL 9005, Straight male connector M12, coding: A, to free cable end, cable length: 5 m

Sensor/actuator cable, 4-position, PVC, black RAL 9005, Plug straight M12, coding: A, on free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm
ConnectorConnection 1
Type Plug straight M12
Number of positions 4
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 5 m
PVC black [PVC]
Dimensional drawing
Cable weight 40 kg/km
UL AWM Style 2464 / 1729 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PVC black [PVC]
Conductor structure signal line 19x 0.15 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.26 mm $\pm 0.05 \text{ mm}$
External cable diameter 4.70 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PVC
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, white, blue, black
Thickness, insulation $\geq \dots$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 5,0-PVC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.