

INDUSTRIAL COMPONENT DATA

SAC-8P-MS/ 0,5-PUR/FS SCO BK 1411963 PHOENIX CONTACT Sensor/Actuator cable, 8-position, PUR halogen-free, bl..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-MS/ 0,5-PUR/FS SCO BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-MS/ 0,5-PUR/FS SCO BK
Catalog number	1411963
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-D0DA296656
Generated	2026-08-05

Product Overview

Sensor/Actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded, Cable length: 0.5 m

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, M12 SPEEDCON straight connector, coding: A, a M12 SPEEDCON straight female, coding: A, cable length: 0.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1411963

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356946827

Weight per Piece (excluding packing) 43.650 g

Custom tariff number 85444290

Country of origin PL (Poland)

ETIM for 1411963 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

8

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

0.5 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

No

Cable type (EF000081)

Multi-core

Vulcanize (EF004115)

No

Material contact body (EF008248)

CuZn

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-25 °C

Rated current In (EF008250)

2 A

Rated voltage (EF000228)

30 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-MS/ 0,5-PUR/FS SCO BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.