

INDUSTRIAL COMPONENT DATA

SAC-8P- 5,0-240/M12FS 0,34 1408856 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-5,0-240/M12FS 0,34



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-5,0-240/M12FS 0,34
Catalog number	1408856
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2E8C91CA71
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 8-Pole, Halogen-Free PUR, Yellow, Free Cable End, to Straight Connecting Female M12, Encoding: A, Cable Length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1408856

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356835022

Weight per Piece (excluding packing) 256.500 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 2 A

Rated voltage 30 V AC

30 V DC

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss

7.027279218eCl@ss 8.027279218eCl@ss 9.027060311

ETIM 3.0EC001855ETIM 5.0EC001855ETIM 6.0EC001855

UNSPSC 6.0131251501UNSPSC 7.090131251501UNSPSC 11...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-5,0-240/M12FS 0,34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.