

INDUSTRIAL COMPONENT DATA

SAC-8P-M8MS/3,0-542/M8FSSH BK 1412953 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M8MS/3,0-542/M8FSSH BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M8MS/3,0-542/M8FSSH BK
Catalog number	1412953
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-CC6076DE25
Generated	2026-08-02

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 8-pole, PVC, yellow, shielded, M8 straight male connector, to M8 straight connection female, cable length: 3 m

Sensor/actuator cable, 8-position, PVC, yellow, shielded, Plug straight M8, coding: A, on Socket straight M8, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard

Number of positions 8

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 1.5 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.2 Nm (M8 connectors)
ConnectorConnection 1
Type Plug straight M8
Number of positions 8
Coding type A
Connection 2
Type Socket straight M8
Number of positions 8
Cable/lineCable length 3 m
PVC yellow 105 °C [542]
Dimensional drawing
Cable weight 58 kg/km
UL AWM Style 2517 (105 °C / 300 V)
Number of positions 8
Shielded yes
Cable type PVC yellow 105 °C [542]
Conductor structure signal line 32x 1.10 mm
AWG signal line 24
Wire diameter incl. insulation 1.12 mm $\pm 0.03 \text{ mm}$
External cable diameter 6.30 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PVC
External sheath, color yellow
Conductor material Tin-plated Cu litz wires
Material, filler PP
Material wire insulation PVC
Single wire, color white, brown, green, yellow, gra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M8MS/3,0-542/M8FSSH BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.