

INDUSTRIAL COMPONENT DATA

SACC-SQ-M12MS-8CON-20-L180 1408574 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-SQ-M12MS-8CON-20-L180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-SQ-M12MS-8CON-20-L180
Catalog number	1408574
Category	Circular connector, mounting (PCB)
Minimum order	10 Pcs
Document ID	EO-9EAF342673
Generated	2026-08-02

Product Overview

Flush-type connector

Conect. plug. to be apar. front wall, Universal, 8-pole, Male connector, straight, M12, coding: A, Front mounting, Square flange, Wave solder contacts, 0.25 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1408574

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 240 (C-2-2013)

GTIN 4046356826457

Weight per Piece (excluding packing) 11.330 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP20

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 2 A

Rated voltage 30 V

Rated surge voltage 0.8 kV

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Signal type/category Universal

Status display No

Overvoltage category III

Degree of pollution 3

Connection method Solder pins

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Front mounting Square flange 20 mm side length

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, tin-plated

Sealing material FKM

Cable

Conductor cross section 0.25 mm²

Conductor stru...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-SQ-M12MS-8CON-20-L180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.