

INDUSTRIAL COMPONENT DATA

SACC-E-M12FS-4CON-M16/0,5 VA 1458855 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12FS-4CON-M16/0,5 VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12FS-4CON-M16/0,5 VA
Catalog number	1458855
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-867BA84909
Generated	2026-08-03

Product Overview

Flush-type connector

Built-in mounting female for sensors/actuators, 4 poles, M12, A-coded, screw-mounted/front wall with M16 thread, with 0.5 m TPE braided cable, 4 x 0.34 mm², stainless steel design

Appliance Connector Front Panel, Universal, 4 Pole, Receptacle, Straight, M12 Standard, Code: A, On Free End Of Wire, Front Wall Mounting, M16 x 1.5, Single Strands, Cable Length: 0.5 m, 0.34 mm², TPE Stranded Wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1458855

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 268 (C-2-2013)

GTIN 4046356655507

Weight per Piece (excluding packing) 18.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length of cable 0.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Standards/regulations M12 connector IEC 61076-2-101

Signal type/category Universal

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Front mounting M16 x 1.5

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material, knurls Stainless steel

Sealing material FKM

Cable

Cable type TPE litz wire

Conductor cross section 0.34 mm²

AWG signal line 22

Conductor s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12FS-4CON-M16/0,5 VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.