

INDUSTRIAL COMPONENT DATA

PTIO 1,5/S/4-LED 24 RD 3244517 PHOENIX CONTACT

Sensor/actuator terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTIO 1,5/S/4-LED 24 RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTIO 1,5/S/4-LED 24 RD
Catalog number	3244517
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-2CBC196640
Generated	2026-08-01

Product Overview

Sensor/actuator terminal block

Terminal block for detectors/actuators, with red light indication, nominal voltage: 250 V, nominal current: 13.5 A, number of connections: 5, connection type: Push-in connection, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3244517

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 39 (C-1-2017)

GTIN 4046356735919

Weight per Piece (excluding packing) 7.800 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 4

Number of connections 5

Potentials 4

Nominal cross section 1.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum load current 13.5 A (with 4 mm² conductor cross section)

Rated surge voltage 4 kV

LED voltage range 15 V AC/DC ... 30 V AC/DC

LED current range 0.31 mA ... 0.95 mA

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)

Maximum load current 13.5 A

Nominal current I_N 13.5 A

Nominal voltage U_N 250 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.14 mm² / 0.2 kg

1.5 mm² / 0.4 kg

Tensile test result Test pas...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTIO 1,5/S/4-LED 24 RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.